

# Platform Specifications



Platform

## Key Features

- Sunlight Readable
- 16:9 Wide
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- Thin and Light
- 30 CCFL

Optional 7H Protective Acrylic Cover



## SLO3212/3215 (AUO T315XW01)

<b>Model No.</b>	SLO3212/SLO3215
<b>LCD Display</b>	32" WXGATFT LCD Module
<b>Display Area</b>	697.68 x 392.26mm
<b>Brightness</b>	500 cd/m <sup>2</sup> / 1000 cd/m <sup>2</sup>
<b>Resolution</b>	1366x768 (WXGA)
<b>Contrast Ratio</b>	800 : 1
<b>Pixel Pitch (mm)</b>	0.51075(H) x 0.51075(V)
<b>Viewing Angle</b>	+88° ~ -88° (H), +88° ~ -88° (V)
<b>Display Colors</b>	16.7M colors
<b>Response Time</b>	20ms (Typical)
<b>Sync</b>	LVDS
<b>Power Consumption</b>	295W
<b>Inverter</b>	BLC-3230A
<b>Control Board (Optional)</b>	AD5621GA (Standard)
<b>F / R Control Button</b>	Power Switch, Menu, Select (+, -), Auto
<b>OSD Menu</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock....
<b>Dimensions (WxHxD)</b>	810x500x109.85mm
<b>Weight</b>	26.5kgs / 3 4.95kgs
<b>Optional</b>	<input checked="" type="checkbox"/> Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

<b>Control Board (Optional)</b>	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
<input checked="" type="checkbox"/> AD5621GA	VGA+Audio
<input checked="" type="checkbox"/> AD5621GD	VGA+DVI
<input checked="" type="checkbox"/> AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
<input checked="" type="checkbox"/> AD1501GDV	VGA+DVI+S-Video
<b>F / R Control Button</b>	5 Key / 4 Key (Optional)
<input checked="" type="checkbox"/> 5 Key	Power Switch, Menu, Select (+, -), Auto
<input checked="" type="checkbox"/> 4 Key	Power Switch, Menu, Select (+, -)

SLO= Open Frame  
SLD= Industrial Casing



