

## ProDVX Lightbox II

The perfect modular instore media system

### Advertising, communications and Information System

With dialogue and information at center stage, your message will always be crystal clear. This principle lies at the very heart of our new **ProDVX Lightbox II** system. Light up what you're communicating with a great eye catching, fully modular, low-voltage system.

### A Bright Concept

The Lightbox Viewer consists of a screen suspended in a low-voltage track. We've integrated new slim LED backlights into the frame that light up the screen. Simply insert your advertising transparencies and get them noticed immediately!

### Moving Pictures

Our full HD LightBox 21,5" and 37" LCD displays with integrated PC or SSD video player will transform your advertising into a movie or a slide show with an audio background. Data is fed into the Lightbox LCD display via a compact flash card (in case of the SSD player) or WiFi in case of the PC version.

### Endless Possibilities

Three Lightbox Viewers in the ROD hanging system, a combination of Lightbox Viewers and LightBox LCD displays fitted in landscape or portrait mode. System integration on the ceiling, simply endless possibilities with one modular system. Our flexible fixture method guarantees that you can arrange your information perfectly in tune with the layout of the location.

*"Combines still images with moving video, a perfect eyecatcher..!"*

Energy friendly power system

Fully customizable

Great aesthetics

Slim design *"New 2011 Model...!"*



## ProDVX Lightbox II

### Specification overview

### Part names:

LightBox II A2 - PC

LightBox II A2 - Viewer

LightBox II A3 - PC

LightBox II A3 - Viewer

LightBox II ROD System

LightBox II Power Supply



### Modular design

All of the Lightbox II modular system parts are available separately, the flexibility of the systems allows for a combination of various ( sized ) displays, placing them in portrait or in landscape mode, best of all; This system gives you complete freedom in arranging your displays to your - or your customers needs !

LBII - A2 - PC	LB2 - A3 - PC	LBII - A2 Viewer	LBII - A3 Viewer
LCD display	LCD display	Static display	Static display
460.89 x 819.36 mm	268.11 x 476.64 mm	460 x 820 mm	270 x 475 mm
400 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	1200 cd/m <sup>2</sup>	1200 cd/m <sup>2</sup>
1920 x 1080	1920 x 1080	-	-
16:9	16:9	16:9	16:9
4000:1	1000:1	-	-
90/90	170	-	-
90/90	160	n.a.	n.a.
LED	LED	LED	LED
in development	in development	in development	in development
IntelR AtomTM N270	IntelR AtomTM N270	-	-
Gene-9315	Gene-9315	-	-
IntelR 945 GSE+ICH7M	IntelR 945 GSE+ICH7M	-	-
1GB DDRII/max 2 GB	1GB DDRII/max 2 GB	-	-
HDD SATA I / + CF	HDD SATA I / + CF	-	-
2 x Gigabyte	2 x Gigabyte	-	-
Optional (WiFi, Bluetooth)	Optional (WiFi, Bluetooth)	-	-
Optional	Optional	-	-
YES, 1 x	YES, 1 x	-	-
YES, 2 x USB 2.0	YES, 2 x USB 2.0	-	-
10% ~ 80% (N.C.)	10% ~ 80% (N.C.)	10% ~ 80% (N.C.)	10% ~ 80% (N.C.)
-20 °C ~ 60 °C	-20 °C ~ 60 °C	-20 °C ~ 60 °C	-20 °C ~ 60 °C
0 °C ~ 50 °C	0 °C ~ 50 °C	0 °C ~ 50 °C	0 °C ~ 50 °C
t.b.d.	t.b.d.	t.b.d.	t.b.d.
ROD II system	ROD II system	ROD II system	ROD II system
Vesa mount	Vesa mount	Vesa mount	Vesa mount
Windows, Linux	Windows, Linux	Windows, Linux	Windows, Linux

### Model name:

Display area:  
Brightness:  
Resolution:  
Aspect ratio:  
Contrast ratio:  
Viewing angle r/l:  
Viewing angle u/d:  
Backlight:  
Touch system:  
CPU support:  
Board type:  
Chipset:  
System memory:  
Storage:  
Ethernet:  
WiFi:  
3G:  
Serial / COM:  
USB ports:  
Operating humidity:  
Storage temp:  
Operating temp:  
Net weight (Kg)  
Mounting:  
Optional:  
Driver support:

