

# POS

## Spanpixel Main Features

- ▶ Sunlight Readable
- ▶ Ultra-Wide Aspect Ratio
- ▶ LED Backlight
- ▶ Lower Power Consumption
- ▶ Fan-less
- ▶ Long Life
- ▶ Slim Bezel
- ▶ Space Limitation

## SSF0622/0822/1022

Model No.	SSF0622	SSF0822	SSF1022
LCD Display	6.4"	8"	10.5"
Display Area (WxH)mm	153.6x50.2	195.1 x 61.2	256 x 78.7
Brightness	300 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
Resolution	1024 x 338	1024 x 324	1366 x 420
Aspect Ratio	16:5	16:5	16:5
Contrast Ratio	400 : 1	500 : 1	500:1
Pixel Pitch(um)	0.15 x 0.15	0.1905 x 0.189	0.1875 x 0.1875
Viewing Angle	140°(H), 110°(V)	140°(H), 110°(V)	90°(H), 65°(V)
Display Color	262K	262K	262K
Response Time	20ms	5ms	7 ms
Backlight	LED Backlight	LED Backlight	LED Backlight
Power Consumption	3W	3W	3.2W
LED Driving Board	On Board	On Board	On Board
AD Board	N/A	N/A	N/A
F/R Control Button	N/A	N/A	N/A
OSD Menu	N/A	N/A	N/A
Dimensions (WxHxD)mm	166.7 x 66.2 x 6.6	215 x 79.2 x 7.5	269.6 x 99.4 x 6.5
Weight	0.13kg	0.17kg	0.32kg
Optional	☑ AOT ☑ Touch		

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

# Gaming

## Applications

- ▶ Button Deck
- ▶ PCT Option Available
- ▶ Player Tracking Display
- ▶ Roulette Display

## SSD1505/1515/1612/1712

Model No.	SSD1505	SSD1515	SSD1612	SSD1712
LCD Display	15.0"	15.9"	16.4"	17.2"
Display Area (WxH)mm	376.3x71.2	376.3x150.5	409.8x76.8	409.8x153.6
Brightness	1000 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>
Resolution	1280x242	1280x512	1366x256	1366x512
Aspect Ratio	16:3	16:6.4	16:3	16:6
Contrast Ratio	1000 : 1	1000 : 1	1000 : 1	1000 : 1
Pixel Pitch(um)	0.294x0.294	0.294x0.294	0.3x0.3	0.3x0.3
Viewing Angle	160°(H), 170°(V)	160°(H), 170°(V)	170°(H), 160°(V)	170°(H), 160°(V)
Display Color	16.7M	16.7M	16.7M	16.7M
Response Time	5ms	5ms	3.7ms	3.7ms
Backlight	LED Backlight	LED Backlight	LED Backlight	LED Backlight
Power Consumption	15W	23W	16W	17W
LED Driving Board	On AD Board	LID15A04	LID16A01	LID17A03
AD Board	AD5621GS	AD2632GD	AD5621GA	AD5621GA
F/R Control Button	4 Key	4 Key	4 Key	4 Key
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....			
Dimensions (WxHxD)mm	408x106.2x37.8	398.4x176.2x52.7	432.9x103.5x40	432.9x179.9x40.5
Weight	1.25kg	2.5kg	1.41kg	1.8kg
Optional	☑ AOT ☑ Touch			

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

# Transportation

## Applications

- ▶ Route Map / Way Finder
- ▶ MRT
- ▶ Airport Schedule
- ▶ Bus
- ▶ Light Rail

## SSD1915/1922/2313/2815

Model No.	SSD1915	SSD1922	SSD2313	SSD2815
LCD Display	19"	19"	23.5"	28"
Display Area (WxH)mm	473.76 x 96.44	476.64x96.3	575x161.8	697.68 x 130.7
Brightness	1000 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup>
Resolution	1680 x 342	1920x388	1366x382	1366 x 256
Aspect Ratio	16:3	16:3.2	16:4.5	16 : 3
Contrast Ratio	2000 : 1	3700 : 1	3000 : 1	2500:1
Pixel Pitch(um)	0.282x0.282	0.248x0.248	0.4215x0.4215	0.51075x0.51075
Viewing Angle	178°(H), 178°(V)	178°(H), 178°(V)	178°(H), 178°(V)	176°(H), 176°(V)
Display Color	16.7M	16.7M	16.7M	16.7M
Response Time	20ms	16ms	6.5ms	6.5 ms
Backlight	LED Backlight	LED Backlight	LED Backlight	LED Backlight
Power Consumption	25W	22.5W	34W	28W
LED Driving Board	LID19A01	LID21A06	On Board	LID28A01
AD Board	AD2662GD	AD2662GD	AD5621GD	AD2662GD
F/R Control Button	4 Key	4 Key	4 Key	4 Key
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....			
Dimensions (WxHxD)mm	496.6 x 126 x 57.3	497.7x125.2x46.1	612.2x198.2x41.5	740.2x167.2x56
Weight	2.3kg	2.4kg	3.25kg	5kg
Optional	☑ AOT ☑ Touch			

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

# Digital Signage

## Applications

- ▶ Retail
- ▶ Restaurant
- ▶ Vending Machine
- ▶ Gas Pump
- ▶ Elevator

## SSD2825/2925/3835/4913

Model No.	SSD2825	SSD2925	SSD3835	SSD4913
LCD Display	28"	29.3"	38"	49.5"
Display Area (WxH)mm	697.7 x 129.7	697.68 x 261.5	930.2 x 243.2	1209.6x338.94
Brightness	1000 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>
Resolution	1366 x 254	1366x512	1920x502	1920x538
Aspect Ratio	16 : 3	16:6	16:4.2	16:4.5
Contrast Ratio	3000:1	2500 : 1	3000 : 1	6000 : 1
Pixel Pitch(um)	0.51x0.51	0.51075x0.51075	0.1615 x 0.4845	0.21 x 0.63
Viewing Angle	178°(H), 178°(V)	176°(H), 176°(V)	176°(H), 176°(V)	176°(H), 176°(V)
Display Color	16.7M	16.7M	16.7M	1073M
Response Time	6.5 ms	6.5ms	8.5ms	6ms
Backlight	LED Backlight	LED Backlight	LED Backlight	LED Backlight
Power Consumption	43W	70W	79W	TBD
LED Driving Board	On Board	LID29A02	On Board	On Board
AD Board	AD2662GD	AD2662GD	AD2662GD	AD2662GD
F/R Control Button	4 Key	4 Key	4 Key	4 Key
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....			
Dimensions (WxHxD)mm	738x176x54.7	740.2x298x60.9	971x286.6x69.7	1237.2 x 388.8 x 68.8
Weight	5.2kg	7kg	7.5kg	TBD
Optional	☑ AOT ☑ Touch			

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.